



Ringe/individuale Bürstenelemente sind zusätzlich zu denen in der Tabelle für zahlreiche Materialien und Abmessungen verfügbar.

ART DER NUTZUNG

Leichtes Entgraten, Satinieren und Polieren von Oberflächen jeder Art. Die Ringe aus abrasivem Nylon sind auch zum Beizen und Rustikalmachen geeignet.

| MM | | INCH | |
|-------------------|--------|-------------------|-------------|
| D mm | 200 | D inch | 8 |
| E mm | 9 | E inch | 3/8 |
| Loch mm | 40-16 | Loch inch | 1-5/8 - 5/8 |
| Max RPM | 6000 | Max RPM | 6000 |
| CO/IS pach | 10 | CO/IS pack | 10 |
| Art. | 40/200 | Art. | 40/200 |
| Gewinde | Stahl | Gewinde | Stahl |
| Ø Gewinde | 0,50mm | Ø Gewinde | 0,020" |

Le dimensioni, le illustrazioni, le caratteristiche tecniche, le referenze e tutti gli altri dati contenuti nel catalogo possono essere modificati da SIT senza preavviso. Tutte le dimensioni riportate sul catalogo sono da considerarsi nominali e, se non diversamente specificato, sono in mm. Diametri, sporgenze e spessori degli insiemi di filamenti, costituenti le spazzole, sono da considerare tali solo approssimativamente.
The dimensions, illustrations, technical characteristics and all other data contained in the catalogue may be changed by SIT without prior notice. All dimensions on the catalogue, unless otherwise specified, are in mm. Diameters, protrusions and thicknesses of sets of filaments forming the brushes are only approximate.