



Scovoli ad elica semplice in acciaio temprato liscio con anima in filo d'acciaio o in Nylon bianco liscio e acciaio ottonato ondulato, meno aggressivi.

Ø 0,60mm - 0,024"

APPLICAZIONE

Pulizia interna di tubi. Gli scovoli in Nylon sono adatti alla pulizia di tubi in acciaio inossidabile.

MM

INCH

A mm	95
D mm	60
L mm	160
Attacco	M12
CO/IS pach	12
Art.	SC 60
Filo	Nylon bianco liscio

A inch	3-3/4
D inch	2-3/8
L inch	6-5/16
Attacco	M12
CO/IS pack	12
Art.	SC 60
Filo	Nylon bianco liscio

Le dimensioni, le illustrazioni, le caratteristiche tecniche, le referenze e tutti gli altri dati contenuti nel catalogo possono essere modificati da SIT senza preavviso. Tutte le dimensioni riportate sul catalogo sono da considerarsi nominali e, se non diversamente specificato, sono in mm. Diametri, sporgenze e spessori degli insiemi di filamenti, costituenti le spazzole, sono da considerare tali solo approssimativamente.
The dimensions, illustrations, technical characteristics and all other data contained in the catalogue may be changed by SIT without prior notice. All dimensions on the catalogue, unless otherwise specified, are in mm. Diameters, protrusions and thicknesses of sets of filaments forming the brushes are only approximate.