




Scovoli in Nylon abrasivo con filamenti a elica singola.

APPLICAZIONE

Sbavatura e finitura all'interno di componenti tubolari, trapanature e fori conici.

sitbrush.com

MM		INCH	
A mm	20	A inch	3/4
D mm	3	D inch	1/8
L mm	100	L inch	4
Gambo mm	1,5	Gambo inch	1/16
Max RPM	800	Max RPM	800
CO/IS pach	10	CO/IS pack	10
Art.	SA 3	Art.	SA 3
Filo	Nylon abrasivo O.A.	Filo	Nylon abrasivo O.A.
Grit	1,5	Grit	1,5

Le dimensioni, le illustrazioni, le caratteristiche tecniche, le referenze e tutti gli altri dati contenuti nel catalogo possono essere modificati da SIT senza preavviso. Tutte le dimensioni riportate sul catalogo sono da considerarsi nominali e, se non diversamente specificato, sono in mm. Diametri, sporgenze e spessori degli insiemi di filamenti, costituenti le spazzole, sono da considerare tali solo approssimativamente.
The dimensions, illustrations, technical characteristics and all other data contained in the catalogue may be changed by SIT without prior notice. All dimensions on the catalogue, unless otherwise specified, are in mm. Diameters, protrusions and thicknesses of sets of filaments forming the brushes are only approximate.