



Scovoli cilindrici per pulizia manuale disponibili in diverse dimensioni e materiali. Negli scovoli manuali SM il diametro del filo varia a seconda del materiale e delle dimensioni dello scovolo.

### APPLICAZIONE

Rimozione dei residui di lavorazioni di foratura; sbavatura di fori trasversali, lisci o filettati; pulizia di cavità e superfici di difficile accesso. Su richiesta, sono disponibili attacchi filettati differenti.

MM		INCH	
<b>A mm</b>	100	<b>A inch</b>	4
<b>D mm</b>	10	<b>D inch</b>	3/8
<b>L mm</b>	300	<b>L inch</b>	11-13/16
<b>CO/IS pack</b>	10	<b>CO/IS pack</b>	10
<b>Art.</b>	SM 10	<b>Art.</b>	SM 10
<b>Filo</b>	Nylon bianco liscio	<b>Filo</b>	Nylon bianco liscio

Le dimensioni, le illustrazioni, le caratteristiche tecniche, le referenze e tutti gli altri dati contenuti nel catalogo possono essere modificati da SIT senza preavviso. Tutte le dimensioni riportate sul catalogo sono da considerarsi nominali e, se non diversamente specificato, sono in mm. Diametri, sporgenze e spessori degli insiemi di filamenti, costituenti le spazzole, sono da considerare tali solo approssimativamente.  
The dimensions, illustrations, technical characteristics and all other data contained in the catalogue may be changed by SIT without prior notice. All dimensions on the catalogue, unless otherwise specified, are in mm. Diameters, protrusions and thicknesses of sets of filaments forming the brushes are only approximate.